



**anti-adhesive to prevent adhesion of concrete and asphalt overspray**  
**slip agent for pressure moulding and extrusion of concrete and clay bricks**

### ***Advantages***

***Repel® 22 is water-based –***

health, safety and environmentally responsible  
protects paints and plastics without softening or swelling  
stable indefinitely when undiluted  
not corrosive to aluminium  
not a DG, not combustible

mild odour – no diesel smell  
low skin and eye irritation

### ***Application and Preparation***

***Repel® 22 may be diluted***

Use only clean low-salts water\* when diluting.  
Use diluted product within 48 hours. Stir before use.

***Repel® 22 is easy to apply –***

by spray, brush or cotton cloth  
coverage 8 – 20m<sup>2</sup> per litre depending on application  
users should experiment to find the optimal film thickness to give reliable release with little or no curtaining or residues and no build-up on repeated applications  
application as a very fine spray coating is preferred

similar viscosity summer and winter

***Preparation of surfaces –***

Surfaces contaminated with petroleum or vegetable oil should be well cleaned before applying. Wash down with hair shampoo or good detergent in water, then rinse well.

Wash waters containing Repel® 22 may be reused in concrete mixtures.

***\*Low-salts water means water with no more than 80 parts per million of total dissolved salts. 80ppm = 80 mg/litre***

***Designed and manufactured by***

***Berryessa Pty Ltd***  
2/74 Morrow Road, Lonsdale  
South Australia 5160  
[www.berryessa.com.au](http://www.berryessa.com.au)  
[richard@berryessa.com.au](mailto:richard@berryessa.com.au)  
0408 656946