



anti-adhesive to prevent adhesion of concrete and asphalt overspray
slip agent for pressure moulding and extrusion of concrete and clay bricks

Advantages

Repel® 22 is water-based –

health, safety and environmentally responsible
protects paints and plastics without softening or swelling
stable indefinitely when undiluted
not corrosive to aluminium
not a DG, not combustible

mild odour – no diesel smell
low skin and eye irritation

Application and Preparation

Repel® 22 may be diluted

Use only clean low-salts water* when diluting.
Use diluted product within 48 hours. Stir before use.

Repel® 22 is easy to apply –

by spray, brush or cotton cloth
coverage 8 – 20m² per litre depending on application
users should experiment to find the optimal film thickness to give reliable release with little or no curtaining or residues and no build-up on repeated applications
application as a very fine spray coating is preferred

similar viscosity summer and winter

Preparation of surfaces –

Surfaces contaminated with petroleum or vegetable oil should be well cleaned before applying. Wash down with hair shampoo or good detergent in water, then rinse well.

Wash waters containing Repel® 22 may be reused in concrete mixtures.

****Low-salts water means water with no more than 80 parts per million of total dissolved salts. 80ppm = 80 mg/litre***

Designed and manufactured by

Berryessa Pty Ltd
2/74 Morrow Road, Lonsdale
South Australia 5160
www.berryessa.com.au
richard@berryessa.com.au
0408 656946