



**water-based anti-adhesive agent
for protection of plant and vehicles
against concrete overspray**

Advantages

Repel® 52 is water-based –

**not combustible mild odour – no diesel smell
not a DG low skin and eye irritation**

Repel® 52 protects metal, plywood and plastics –

protects paints and plastics without softening or swelling

Application and Preparation

Repel® 52 is easy to apply –

**by spray, brush or cotton cloth similar viscosity summer and winter
stable indefinitely when undiluted may be diluted with low-salts* water
coverage 6 – 20m² per litre depending on application
users should experiment to find the optimal film thickness to give reliable release
with little or no curtaining or residues and no build-up on repeated applications
application as a very fine spray coating is preferred**

Preparation of surfaces –

**Surfaces contaminated with petroleum or vegetable oil should be well cleaned before
applying. Wash down with hair shampoo or good detergent in water, then rinse well.**

Wash waters containing Repel® 52 may be reused in concrete mixtures.

****Low-salts water means water with no more than 80 parts
per million of total dissolved salts. 80ppm = 80 mg/litre***

Designed and manufactured by

Berryessa Pty Ltd
2/74 Morrow Road,
Lonsdale South Australia 5160
www.berryessa.com.au
richard@berryessa.com.au
0408 656946